

STANDARD



- Full D1 real-time recording all 4 channels, H.264 compression
- True pentaplex operation: Record during Search, Playback, Setup, Backup, and when Networked
- USB mouse support
- Backup to internal DVD-RW or external devices
- CMS (Central Monitoring System) software included
- Supports most popular PTZ protocols
- Self-diagnosis and notification of system status with S.M.A.R.T protocol
- Remote control included
- 2-year warranty



Channels	4
Compression	H.264
Camera inputs	4
Monitor outputs	1 Composite BNC, 1 VGA, 1 Spot BNC
Display / Recording Frame	120fps (100fps PAL)
Recording Resolution	720×480, 720×240, 360×240 (NTSC)
OS	Embedded Linux
Pentaplex	Live, Recording, Playback, Networking, Backup at the same time
Sensor in / Alarm out	4in / 1out
Audio	4 in / 1 out (G.723 Compression)
Display Split	1,4
System Control	Front Buttons, IR Remote Controller, Mouse
Recording Modes	Normal, Event, Sensor, Schedule
Recording Quality	Level 1, 2, 3
Search Mode	Date & Time, Event (Motion, Sensor)
PTZ Control	RS-485
Backup	CD/DVD-RW (option), USB 2.0, Memory Stick
Control Unit	IR Remote Control, Mouse Supported (mouse not included)
Storage	Max. 4 SATA HDD (factory installed)
USB	USB 2.0 - 1 Front, 1 Rear
Network	10/100M Base-T Ethernet, LAN, WAN, Web, DHCP/DDNS, Static/Dynamic IP
Remote Monitoring S/W	CMS, Agent, Web viewer, PDA viewer
Power	100/240VAC, 60/50Hz, 1.6A
Dimensions (w/h/d), Weight	15.6 × 2.8 × 15.4 inches (395 × 70 × 390 mm), Approx 11 lbs. (5kg)

HDD Size	Model
No HDD	RD412
250GB	RD412-250
500GB	RD412-500
1TB	RD412-1TB
2TB	RD412-2TB
DVD/RW	Add "D" to end of model number to add DVD/RW drive